








Filters		Part No.	Hose barb		Weight
			mm	in.	g
113 AU NZ	<b>Plastic Detergent</b>  Intake stainer	M0211000120 Model MV 15 M0211000110 Model MV 16	6-8	-	12
	<b>Stainless Steel Strainer</b> 	E29.0915.00	7	0,27	18
	<b>Plastic Strainer</b> 	E28.1010.00	7	0,27	20
116 AU	<b>Plastic Strainer with check valve</b> 	E28.1000.00	7	0,27	22
	<b>Strainers</b>		<b>Part No.</b>		<b>Intake</b>
117 AU NZ	<b>Aluminium Intake Strainer</b> FA1 	E28.0010.10	G 1/2 F-M		220
	<b>Plastic Intake Strainer</b> F5 	E29.0300.20	G 1/2 F-F		20




Strainers		Part No.	Intake	Weight
119 AU	<b>Intake Strainer</b> FYO 	E28.0160.00	G 3/8 FF	130
		E28.0162.00	G 1/2 FF	150
		E28.0164.00	G 3/4 FF	240
120 AU	<b>"Y" Brass Strainer</b> 	M0211000530	G 3/4 F inlet G 3/4 F outlet	225



Foam Lances	Part No.	Nozzle	Rated Pressure		Max Pressure		Max Vol.	Max Temp.
		mm	bar	p.s.i.	bar	p.s.i.	l/min	° C
121 AU NZ	<b>Foam Injector with Tank</b>  LS3 E25.1500.12	1.25	160	2300	180	2600	20	60
		1.5	140	2000	150	2150	25	65
122 AU NZ	<b>Foam Injector</b>  LS10 E29.0800.00 E29.0800.15	1.5	140	2000	150	2150	25	65
123 AU	<b>Foam Injector with Tank</b>  LS10 E29.0820.00	1.5	140	2000	150	2150	25	65

Foam Lances		Part No.	Nozzle	Rated Pressure		Max Pressure		Max Vol.	Max Temp.
			mm	bar	p.s.i.	bar	p.s.i.	l/min	° C
124 AU	<b>Foam Injector</b>  LS12	E25.1800.15	1.5	200	2900	220	3200	25	60
	<b>Foam Injector with Tank</b>  LS12	E25.1820.15	1.5	200	2900	220	3200	25	60




Electrical		Part No.	Connection	Pressure On		Max Pressure		Power		Max Temp.
				bar	p.s.i.	bar	p.s.i.	V	A	° C
126 AU NZ	<b>PR5</b>  Pressure Switch	E29.0080.00	G 1/4 M	25	360					90
		E29.0080.10	G 1/4 M	15	220	280	4050	250	5	
		E29.0080.50	G 1/4 M	40	580					
127 AU NZ	<b>FL3</b>  Flow Switch	E28.0500.00	G 3/8 M (inlet)	-	-	280	4050	250	1	80
128 AU	<b>MV 60</b>  Flow Switch	Vertical M0205010000	G 3/8 F inlet	-	-	300	4350	12	0.8	80
		Horizontal M0205010010	G3/8 F outlet					- 250		

Electrical	Part No.	Connection	Pressure On		Max Pressure		Power		Max Temp.	
			bar	p.s.i.	bar	p.s.i.	V	A	° C	
129 AU	 <b>PR1</b> Pressure Switch	E29.0000.00	G 3/8	45	650	450	6500	250	15	90
130	 <b>PR16</b> Pressure Switch	E29.0035.10 E29.0035.15	G 3/8 G 3/8	40 250	580 360	280	4050	250	15	90

Electrical	Part No.	Dimensions	Weight	Max Pressure		Power		Max Temp.	
			g	bar	p.s.i.	V	A	° C	
131 AU	 <b>DA</b> Discaling electric Injector	E12.5010.00	-	24 g/h	0.5	7	24	-	-
132 AU	 <b>Tank</b> for discaling pump	E14.6501.00	L1 Usg 0.26	108	-	-	-	-	-
133 AU	 <b>Thermostat</b>	E12.5050.00	900 mm coil length 6.5x95mm probe	150	-	-	240	15	-

Tanks		Part No.	Connection	Max Pressure		Weight	Max Temp.
				bar	p.s.i.	g	° C
134 AU	<b>Tank 1USg</b>  4 Litres	E28.2000.15	2 holes	-	-	470	60
		E28.2000.15	3 holes			470	
135 AU	<b>Complete Tank 1USg</b>  4 Litres	E28.2020.00	G 3/8 M 20 mm hose barb	-	-	850	60
136 AU	<b>Intake strainer for tank</b> 	E28.0080.23	G 3/8 M	-	-	70	-
137 AU NZ	<b>RGP</b>  Plastic float value	E29.0150.00	G 3/4 M	10	145	80	60
138 AU NZ	<b>RGO</b>  Brass float value	E29.0160.00 E29.0160.20	G 3/8 M G 3/4 M	10	145	245 260	60

Other Accessories		Part No.	Connection	Max Pressure		Weight	Max Temp.
				bar	p.s.i.	g	° C
139 AU	<b>Dampener</b> 	E29.0200.05	3/8 Npt F 0.1L volume	210	3050	1400	80
		E28.0202.05	1/2 Npt F 0.35L volume				
140 AU NZ	<b>Rotating Brush</b>  SR8	E29.0500.20 white bristle	3 mm Nozzle	30	435	770	60
		E29.0550.00 black bristle					
141 AU NZ	<b>Fixed Brush</b>  SP4	E29.0561.00	-	5	71	206	40
		E29.0562.00					
142 AU NZ	<b>Pressure Gauges</b> 	E13.0025.16	G 1/4 Rad.	-	-	165	-
		E13.0025.25	G 1/4 Rad.			165	
		E13.0025.40	G 1/4 Rad.			165	
		E13.0035.16	G 1/4 Pst/Bck			170	
		E13.0035.25	G 1/4 Pst/Bck			170	
		E13.0035.40	G 1/4 Pst/Bck			170	
		E13.0044.00	Flange			10	
E13.0054.00	Bracket	18					
143 AU NZ	<b>Cap &amp; Filter for diesel tank</b> 	E29.0197.84	40 mm	-	-	24	-

Other Accessories		Part No.	Connection	Max Pressure		Weight	Max Temp.
				bar	p.s.i.	g	° C
144 AU	<b>Brass Elbow</b> 	E12.2006.00	3/8M 3/8M	250	3650	80	-
		E12.2008.00	3/8F 3/8F			118	
		E12.2010.00	3/8M 3/8F			85	
		E12.2012.00	3/8M 1/4M			85	
		E12.2014.00	3/8M 1/4F			85	
		E12.2022.00	1/2M 1/4F			118	
145 AU	<b>TII Connection</b> 	E12.2050.00	3/8 F.F.F	250	3650	130	-
		E12.2050.20	3/8 F.F - 1/4M			125	
		E12.2055.00	3/8 F.F - 3/8M			125	
146 AU NZ	<b>Tank Cleaning Head with motor</b>  M21E (550 mm)	E25.4300.00	14-M22x1.5M 2 x M4 Nozzle	250	3650	3200	90