


Interpump - PSI 1750-2200




Version V
(built in unloader
and venturi)



Version A
(electric motor)



Version B
(electric motor)



Version C
(petrol motor)

Pump type	Volume		Pressure		r.p.m. - g/min.	HP
	l/min	G.P.M.	bar	p.s.i.		
W1507	7	1.9	150	2200	1450	3
W1208	8	2.1	120	1750		2.5
W1210	10	2.6	120	1750		3
T1508	8	2.1	150	2200	1750	3
T1209	9	2.4	120	1750		3
T1212	12	3.2	120	1750		4
WW1508	8	2.1	150	2200	2800	3
WW1509	9	2.4				3.5
WW1510	10	2.6				4
WW1511	11	2.9				4.5
WW1513	13	3.4				5

Kerrick

TT1508	8	2.1	150	2200	3400	3
TT1510	10	2.6				4
TT1511	11	2.9				4
TT1512	12	3.2				4.5
TT1513	13	3.4				5

* Technical specifications and pictures are indicative and are subject to changes without notice.
All models can be supplied with built-in automatic pressure regulator and venturi (version V)

Version A	T1508
	T1209
	T1212
	r.p.m. - g/min.
	1750
ELECTRIC MOTOR	

Version B	W1507	WW1508
	W1208	WW1510
	W1210	WW1511
		WW1511
	r.p.m. - g/min.	
	1450	2800
ELECTRIC MOTOR		

Version C	TT1508
	TT1510
	TT1511
	TT1512
	TT1513
	r.p.m. - g/min.
	3400
PETROL ENGINE	