


* Fissare con Loctite 542 col. ROSSO
 * Affix with Loctite 542 col. RED
 * Fixer avec de la Loctite 542 couleur ROUGE
 * Mit Loctite 542 ROT befestigen
 * Fijar con Loctite 542 col. ROJO
 * Fixar com Loctite 542 cor. VERMELHA
 ** Lubrificare con grasso al silicone OCILIS 250
 ** To lubricate with silicon grease OCILIS 250
 ** Lubrifier avec gras à la silicone OCILIS 250
 ** Sich mit fett zum Silikon OCILIS 250 schmieren
 ** Para lubricar con la grasa al silicón OCILIS 250
 ** Para lubrificar com a graxa ao silicone OCILIS 250



HT

SERIE 47

DIS. COD. 47.9521.00

**KERRICK®****HT4715 – HT4718
HT4721 – HT4723**

POS	COD.	DESCRIZIONE – DESCRIPTION – KIT	NR
1	47.1209.41	Testata Ø 22 - NICKEL	1
2	99.3206.00	Vite M8x70 UNI 5737	8
3	96.7020.00	Rosetta Ø 8 UNI 1736	8
4	90.5105.00	Anello antiest. Ø 17.4x21.9x1.8	201
5	90.3400.00	Anello tenuta Ø 17.1x22.3x1.8	201
6	36.2003.66	Sede valvola	201
7	36.2001.76	Valvola	201
8	94.7376.00	Molla Ø 9.4x14.8 INOX	201
9	36.2002.51	Guida valvola	201
10	90.3847.00	OR Ø 20.24x2.62 (3081) – 90 Sh.	5
11	98.2222.00	Tappo M24x2x16.5 - NICKEL	5
12	36.7049.01	Gruppo valvola aspiraz. / mand.	201
13	99.3039.00	Vite M8x16 UNI 5931	8
14	47.1512.22	Coperchio cuscinetto	1
15	90.3913.00	OR Ø 67.95x2.62 (3268)	2
16	91.8378.00	Cuscinetto a rulli 32206	2
17	90.1625.00	Anello rad. Ø 22x32x6.5	2
18	90.9126.00	Boccola Ø 22x25x30	3
19	47.0100.22	Carter pompa	1
20	98.2106.00	Tappo carico olio G 3/8"	1
21	90.3922.00	OR Ø 133.02x2.62 (3525)	1
22	47.0219.35	Albero – HT4715	1
	47.0218.35	Albero – HT4718	1
	47.0221.35	Albero – HT4721	1
	47.0224.35	Albero – HT4723	1

KIT RICAMBI – SPARE KITS

KIT Nr.	KIT 2	KIT 3	KIT 5	KIT 6	KIT 201	KIT 202	KIT 203
Posizioni include Positions included	17	42	10 - 11	32 - 35 37 - 38 39	4 - 5 6 - 7 8 - 9 (12)	45 - 47	43 - 44 45 - 46 47
Nr. Pcs.	3	2	6	3	6	3	1

POS	COD.	DESCRIZIONE – DESCRIPTION – KIT	NR
23	91.4892.00	Linguetta 9x7x35 UNI 6604	1
24	90.0557.00	Anello di fermo Ø 12	6
25	97.7380.00	Spinotto Ø 13x35.5	3
26	47.0504.66	Guida pistone	3
27	47.0300.01	Biella completa	3
28	99.1912.00	Vite M6x30 UNI 5931	5
29	47.1601.22	Coperchio posteriore	1
30	97.5968.00	Spia livello olio G 3/4"	2
31	98.2042.50	Tappo G 1/4"x9	1
32	90.3585.00	OR Ø 10.82x1.78 (2043)	6
33	99.3099.00	Vite M8x35 UNI 5931	6
35	96.7286.00	Rosetta Ø 14x28x0.5	6
36	47.0405.09	Pistone Ø 22	3
37	90.5067.00	Anello antiest. Ø 11x14x1.5	6
38	96.7280.00	Rosetta Ø 14x18.5x0.5	6
39	47.2195.66	Vite fissaggio pistone	6
40	47.1510.22	Coperchio cuscinetto	1
41	97.5678.00	Spessore	2
42	90.1648.00	Anello rad. Ø 30x55x7	3
43	90.3616.00	OR Ø 34.65x1.78 (2137)	203
44	47.0814.70	Anello di fondo Ø 22	203
45	90.2300.00	Anello ten. alt. Ø 22x28.15 LP	202-203
46	47.2175.70	Anello intermedio Ø 22	203

POS	COD.	DESCRIZIONE – DESCRIPTION – KIT	NR
47	90.2310.00	Anello ten. alt. Ø22x35x9	202-203
48	47.2000.74	Piedino	2
49	99.3644.00	Vite M10x18 UNI 5931	4
50	96.7106.00	Rosetta Ø 10 DIN 7980	4
51	98.2179.00	Tappo G 1/2"x10 - NICKEL	1
52	96.7514.00	Rosetta Ø 21.5x27x1.5	1
53	98.2099.00	Tappo G 3/8"x13 - NICKEL	1
54	96.7380.00	Rosetta Ø 17.5x23x1.5	1
55	70.2118.01	Spia livello olio	1
56	90.0756.00	Anello di fermo Ø45	1
57	90.3877.00	OR Ø 39.34x2.62 (3156)	1